

# SAFETY DATA SHEET

**Shell GTL Fluid G70**

Print Date 16.06.2022

Revision Date 15.06.2022

Version 1.4

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Trade name : Shell GTL Fluid G70  
Product code : 002D7382  
CAS-No. : 848301-67-7

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Solvent.  
Uses advised against :  
This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : **Shell International Trading Middle East**  
P.O. Box 16968  
. Jebel Ali – Dubai  
United Arab Emirates  
Telephone : + 971 4 3316 500  
Telefax :

### 1.4 Emergency telephone number

: +44 151 350 4595

---

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### GHS Classification

Flammable liquids : Category 4  
Aspiration hazard : Category 1

### 2.2 Label elements

#### GHS-Labeling

# SAFETY DATA SHEET

## Shell GTL Fluid G70

Print Date 16.06.2022

Revision Date 15.06.2022

Version 1.4

Hazard pictograms

:



Signal word

: Danger

Hazard statements

: PHYSICAL HAZARDS:  
H227 Combustible liquid.  
HEALTH HAZARDS:  
H304 May be fatal if swallowed and enters airways.  
ENVIRONMENTAL HAZARDS:  
Not classified as an environmental hazard under GHS criteria.

Precautionary statements

: **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P243 Take action to prevent static discharges.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**  
P370 + P378 In case of fire: Use appropriate media to extinguish.  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P331 Do NOT induce vomiting.  
**Storage:**  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
**Disposal:**  
P501 Dispose of contents and container to appropriate waste site or reclaimer in accordance with local and national regulations.

### 2.3 Other hazards

May ignite on surfaces at temperatures above auto-ignition temperature.  
Vapour in the headspace of tanks and containers may ignite and explode at temperatures exceeding auto-ignition temperature, where vapour concentrations are within the flammability range.  
This material is a static accumulator.  
Even with proper grounding and bonding, this material can still accumulate an electrostatic charge.  
If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur.  
Electrostatic charges may be generated during pumping. Electrostatic discharge may cause fire.

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

#### Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates (Fischer-Tropsch),	848301-67-7	100

# SAFETY DATA SHEET

## Shell GTL Fluid G70

Print Date 16.06.2022

Revision Date 15.06.2022

Version 1.4

C8-26 - Branched and  
Linear

### SECTION 4: First aid measures

#### 4.1 Description of first aid measures

- General advice : Not expected to be a health hazard when used under normal conditions.
- Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
- If inhaled : No treatment necessary under normal conditions of use.  
If symptoms persist, obtain medical advice.
- In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.  
If persistent irritation occurs, obtain medical attention.
- In case of eye contact : Flush eye with copious quantities of water.  
Remove contact lenses, if present and easy to do. Continue rinsing.  
If persistent irritation occurs, obtain medical attention.
- If swallowed : Call emergency number for your location / facility.  
If swallowed, do not induce vomiting: transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.  
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

#### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Not considered to be an inhalation hazard under normal conditions of use.
- No specific hazards under normal use conditions.
- Defatting dermatitis signs and symptoms may include a burning sensation and/or a dried/cracked appearance.
- If material enters lungs, signs and symptoms may include coughing, choking, wheezing, difficulty in breathing, chest congestion, shortness of breath, and/or fever.  
If any of the following delayed signs and symptoms appear within the next 6 hours, transport to the nearest medical facility: fever greater than 101° F (38.3°C), shortness of breath, chest congestion or continued coughing or wheezing.

# SAFETY DATA SHEET

**Shell GTL Fluid G70**

Print Date 16.06.2022

Revision Date 15.06.2022

Version 1.4

## 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.  
Call a doctor or poison control center for guidance.  
Potential for chemical pneumonitis.  
Do not induce vomiting.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.  
Unsuitable extinguishing media : Do not use water in a jet.

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Clear fire area of all non-emergency personnel. Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorganic compounds. Flammable vapours may be present even at temperatures below the flash point.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).  
Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Further information : Keep adjacent containers cool by spraying with water.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Observe all relevant local and international regulations. Local authorities should be advised if significant spillages cannot be contained. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Avoid contact with skin, eyes and clothing. Do not breathe fumes, vapour. Evacuate the area of all non-essential personnel. Take precautionary measures against static discharges.

# SAFETY DATA SHEET

## Shell GTL Fluid G70

Print Date 16.06.2022

Revision Date 15.06.2022

Version 1.4

### 6.2 Environmental precautions

Environmental precautions : Shut off leaks, if possible without personal risks. Remove all possible sources of ignition in the surrounding area. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Attempt to disperse the vapour or to direct its flow to a safe location for example by using fog sprays. Take precautionary measures against static discharge. Ensure electrical continuity by bonding and grounding (earthing) all equipment.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely. Prevent from spreading or entering into drains, ditches or rivers by using sand, earth, or other appropriate barriers. For small liquid spills (< 1 drum), transfer by mechanical means to a labeled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove contaminated soil and dispose of safely.

### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,  
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

## SECTION 7: Handling and storage

General Precautions : Avoid breathing of or direct contact with material. Only use in well ventilated areas. Wash thoroughly after handling. For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.  
Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.  
Ensure that all local regulations regarding handling and storage facilities are followed.  
For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier.

# SAFETY DATA SHEET

## Shell GTL Fluid G70

Print Date 16.06.2022

Revision Date 15.06.2022

Version 1.4

### 7.1 Precautions for safe handling

- Advice on safe handling : Avoid inhaling vapour and/or mists.  
Avoid prolonged or repeated contact with skin.  
Extinguish any naked flames. Do not smoke. Remove ignition sources. Avoid sparks.  
Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.  
Bulk storage tanks should be diked (bunded).  
When using do not eat or drink.
- Product Transfer : Even with proper grounding and bonding, this material can still accumulate an electrostatic charge. If sufficient charge is allowed to accumulate, electrostatic discharge and ignition of flammable air-vapour mixtures can occur. Be aware of handling operations that may give rise to additional hazards that result from the accumulation of static charges. These include but are not limited to pumping (especially turbulent flow), mixing, filtering, splash filling, cleaning and filling of tanks and containers, sampling, switch loading, gauging, vacuum truck operations, and mechanical movements. These activities may lead to static discharge e.g. spark formation. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge ( $\leq 1$  m/s until fill pipe submerged to twice its diameter, then  $\leq 7$  m/s). Avoid splash filling.

Refer to guidance under Handling section.

### 7.2 Conditions for safe storage, including any incompatibilities

- Other data : Drum and small container storage: Drums should be stacked to a maximum of 3 high. Use properly labeled and closable containers. Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat. Tank storage: Tanks must be specifically designed for use with this product. Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions. Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable. Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

# SAFETY DATA SHEET

## Shell GTL Fluid G70

Print Date 16.06.2022

Revision Date 15.06.2022

Version 1.4

- Packaging material : **Suitable material:** Examples of suitable materials are: high density polyethylene (HDPE), polypropylene (PP), and Viton (FKM), which have been specifically tested for compatibility with this product. For container linings, use amine-adduct cured epoxy paint. For seals and gaskets use: graphite, PTFE, Viton A, Viton B.  
**Unsuitable material:** Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Examples of materials to avoid are: natural rubber (NR), nitrile rubber (NBR), ethylene propylene rubber (EPDM), polymethyl methacrylate (PMMA), polystyrene, polyvinyl chloride (PVC), polyisobutylene. However, some may be suitable for glove materials.
- Container Advice : Do not cut, drill, grind, weld or perform similar operations on or near containers. Containers, even those that have been emptied, can contain explosive vapours.

### 7.3 Specific end use(s)

- Specific use(s) : Not applicable

See additional references that provide safe handling practices for liquids that are determined to be static accumulators: American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practices on Static Electricity).  
IEC/TS 60079-32-1: Electrostatic hazards, guidance

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

None established.

#### Biological occupational exposure limits

No biological limit allocated.

#### Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact

# SAFETY DATA SHEET

## Shell GTL Fluid G70

Print Date 16.06.2022

Revision Date 15.06.2022

Version 1.4

the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods

<http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods

<http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances

<http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany

<http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

### 8.2 Exposure controls

**Engineering measures** The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Use sealed systems as far as possible.

Adequate explosion-proof ventilation to control airborne concentrations below the exposure guidelines/limits.

Local exhaust ventilation is recommended.

Eye washes and showers for emergency use.

General Information:

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.

Practice good housekeeping.

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or for subsequent recycle.

Do not ingest. If swallowed, then seek immediate medical assistance.

### Personal protective equipment

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. When prolonged or frequent repeated contact occurs. Nitrile rubber. For incidental



# SAFETY DATA SHEET

## Shell GTL Fluid G70

Print Date 16.06.2022

Revision Date 15.06.2022

Version 1.4

contact/splash protection - Neoprene rubber. PVC.

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material.

Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

**Skin and body protection** : For prolonged or repeated exposures use impervious clothing over parts of the body subject to exposure. Skin protection is not required under normal conditions of use. If repeated and/or prolonged skin exposure to the substance is likely, then wear suitable gloves tested to relevant Standard, and provide employee skin care programmes. If material is handled such that it could be splashed into eyes, protective eyewear is recommended. Personal protection through wearing a tightly closed chemical protection suit and a self-contained breathing apparatus. It is good practice to wear chemical resistant gloves.

**Respiratory protection** : If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g. airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter.

Select a filter suitable for the combination of organic gases and vapours and particles [Type A/Type P boiling point >65°C (149°F)].

**Thermal hazards** : Not applicable

# SAFETY DATA SHEET

**Shell GTL Fluid G70**

Print Date 16.06.2022

Revision Date 15.06.2022

Version 1.4

## Environmental exposure controls

General advice : Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.  
Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.  
Information on accidental release measures are to be found in section 6.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : colourless

Odour : Paraffinic

Odour Threshold : Data not available

pH : Not applicable

Melting point/freezing point : Data not available

pour point : -21 °C Method: ASTM D5950

Boiling point/boiling range :  $\geq 150$  °C Method: Unspecified

Flash point :  $\geq 65$  °C  
Method: Unspecified

Evaporation rate : Data not available

Flammability

Lower explosion limit and upper explosion limit / flammability limit

Upper explosion limit : Data not available

Lower explosion limit : Data not available

Vapour pressure : 0,001 kPa (25,0 °C)  
Method: Unspecified

(50,0 °C)  
Method: Unspecified  
Not applicable

Density : 779 - 781 kg/m<sup>3</sup> (20 °C)  
Method: Unspecified

# SAFETY DATA SHEET

## Shell GTL Fluid G70

Print Date 16.06.2022

Revision Date 15.06.2022

Version 1.4

### Solubility(ies)

Water solubility	: negligible
Solubility in other solvents	: Data not available
Partition coefficient: n-octanol/water	: Data not available
Decomposition temperature	: Data not available

### Viscosity

Viscosity, kinematic	: Method: Unspecified Not applicable  ≤ 7 mm <sup>2</sup> /s (40,0 °C) Method: Unspecified  Method: Unspecified Not applicable
Explosive properties	: no data available
Oxidizing properties	: Data not available

## 9.2 Other information

Conductivity	: Low conductivity: < 100 pS/m, The conductivity of this material makes it a static accumulator., A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10,000 pS/m., Whether a liquid is nonconductive or semiconductive, the precautions are the same., A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid
--------------	---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

### 10.2 Chemical stability

No hazardous reaction is expected when handled and stored according to provisions

### 10.3 Possibility of hazardous reactions

Hazardous reactions	: Reacts with strong oxidising agents.
---------------------	--

### 10.4 Conditions to avoid

# SAFETY DATA SHEET

## Shell GTL Fluid G70

Print Date 16.06.2022

Revision Date 15.06.2022

Version 1.4

Conditions to avoid : Avoid heat, sparks, open flames and other ignition sources.  
In certain circumstances product can ignite due to static electricity.

### 10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

### 10.6 Hazardous decomposition products

Hazardous decomposition products : Hazardous decomposition products are not expected to form during normal storage.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

Information on likely routes of exposure : Exposure may occur via inhalation, ingestion, skin absorption, skin or eye contact, and accidental ingestion.

#### Acute toxicity

##### Components:

##### **Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:**

Acute oral toxicity : LD50 Rat: > 5.000 mg/kg  
Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : LC50 : > 5 mg/l  
Exposure time: 4 h  
Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 Rat: > 2.000 mg/kg  
Remarks: Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

##### Components:

##### **Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:**

Remarks: Not irritating to skin., Based on available data, the classification criteria are not met.

#### Serious eye damage/eye irritation

##### Components:

##### **Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:**

# SAFETY DATA SHEET

## Shell GTL Fluid G70

Print Date 16.06.2022

Revision Date 15.06.2022

Version 1.4

Remarks: Not irritating to eye., Based on available data, the classification criteria are not met.

### Respiratory or skin sensitisation

#### Components:

##### **Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:**

Remarks: Not a sensitiser., Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

#### Components:

##### **Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:**

Genotoxicity in vitro : Remarks: Based on available data, the classification criteria are not met.

: Remarks: Not mutagenic., Based on available data, the classification criteria are not met.

### Carcinogenicity

#### Components:

##### **Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:**

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Distillates (Fischer-Tropsch), C8-26 - Branched and Linear	No carcinogenicity classification.

### Reproductive toxicity

#### Components:

##### **Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:**

Remarks: Does not impair fertility., Not a developmental toxicant., Based on available data, the classification criteria are not met.

### STOT - single exposure

#### Components:

##### **Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:**

Remarks: High concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea., Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

**Shell GTL Fluid G70**

Print Date 16.06.2022

Revision Date 15.06.2022

Version 1.4

## STOT - repeated exposure

### Components:

#### **Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:**

Remarks: Based on available data, the classification criteria are not met.

## Aspiration toxicity

### Components:

#### **Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:**

Aspiration into the lungs when swallowed or vomited may cause chemical pneumonitis which can be fatal.

## Further information

### Components:

#### **Distillates (Fischer-Tropsch), C8-26 - Branched and Linear:**

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Components:

##### **Distillates (Fischer-Tropsch), C8-26 - Branched and Linear :**

Toxicity to fish (Acute toxicity) : LL50 : > 100 mg/l  
Remarks: Based on available data, the classification criteria are not met.

Toxicity to daphnia and other aquatic invertebrates (Acute toxicity) : LL50 : > 100 mg/l  
Remarks: Based on available data, the classification criteria are not met.

Toxicity to algae (Acute toxicity) : LL50 : > 100 mg/l  
Remarks: Based on available data, the classification criteria are not met.

Toxicity to bacteria (Acute toxicity) : LL50 : > 100 mg/l  
Remarks: Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic toxicity) : NOEC: 100 mg/l  
Remarks: Based on available data, the classification criteria

# SAFETY DATA SHEET

## Shell GTL Fluid G70

Print Date 16.06.2022

Revision Date 15.06.2022

Version 1.4

are not met.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 32 mg/l  
Remarks: Based on available data, the classification criteria are not met.

### 12.2 Persistence and degradability

#### Product:

Biodegradability : Remarks: Not Persistent per IMO criteria., International Oil Pollution Compensation (IOPC) Fund definition: "A non-persistent oil is oil, which, at the time of shipment, consists of hydrocarbon fractions, (a) at least 50% of which, by volume, distills at a temperature of 340°C (645°F) and (b) at least 95% of which, by volume, distills at a temperature of 370°C (700°F) when tested by the ASTM Method D-86/78 or any subsequent revision thereof."

#### Components:

##### **Distillates (Fischer-Tropsch), C8-26 - Branched and Linear :**

Biodegradability : Biodegradation: 80 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Readily biodegradable., Oxidises rapidly by photo-chemical reactions in air.

### 12.3 Bioaccumulative potential

#### Product:

Partition coefficient: n-octanol/water : Remarks: Data not available

#### Components:

##### **Distillates (Fischer-Tropsch), C8-26 - Branched and Linear :**

Bioaccumulation : Remarks: Contains constituents with the potential to bioaccumulate.

### 12.4 Mobility in soil

#### Components:

##### **Distillates (Fischer-Tropsch), C8-26 - Branched and Linear :**

Mobility : Remarks: Floats on water., Partly evaporates from water or soil surfaces, but a significant proportion will remain after one day., Large volumes may penetrate soil and could contaminate groundwater.

### 12.5 Results of PBT and vPvB assessment

no data available

### 12.6 Other adverse effects

#### Components:

# SAFETY DATA SHEET

**Shell GTL Fluid G70**

Print Date 16.06.2022

Revision Date 15.06.2022

Version 1.4

## **Distillates (Fischer-Tropsch), C8-26 - Branched and Linear :**

Additional ecological  
information

: Films formed on water may affect oxygen transfer and  
damage organisms.

## **SECTION 13: Disposal considerations**

### **13.1 Waste treatment methods**

Product

: Recover or recycle if possible.  
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.  
Do not dispose into the environment, in drains or in water courses  
Do not dispose of tank water bottoms by allowing them to drain into the ground. This will result in soil and groundwater contamination.  
Waste arising from a spillage or tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.  
MARPOL - see International Convention for the Prevention of Pollution from Ships (MARPOL 73/78) which provides technical aspects at controlling pollutions from ships.

Contaminated packaging

: Drain container thoroughly.  
After draining, vent in a safe place away from sparks and fire.  
Residues may cause an explosion hazard.  
Do not puncture, cut, or weld uncleaned drums.  
Send to drum recoverer or metal reclaimer.  
Comply with any local recovery or waste disposal regulations.  
Do not pollute the soil, water or environment with the waste container.

Local legislation

## **SECTION 14: Transport information**

### **14.1 UN number**

ADR  
IMDG  
IATA

: Not regulated as a dangerous good  
: Not regulated as a dangerous good  
: Not regulated as a dangerous good

### **14.2 Proper shipping name**

ADR  
IMDG  
IATA

: Not regulated as a dangerous good  
: Not regulated as a dangerous good  
: Not regulated as a dangerous good



# SAFETY DATA SHEET

**Shell GTL Fluid G70**

Print Date 16.06.2022

Revision Date 15.06.2022

Version 1.4

## 14.3 Transport hazard class

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

## 14.4 Packing group

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good  
IATA : Not regulated as a dangerous good

## 14.5 Environmental hazards

ADR : Not regulated as a dangerous good  
IMDG : Not regulated as a dangerous good

## 14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

## 14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

---

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other regulations : The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

---

## SECTION 16: Other information

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances

ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council

# SAFETY DATA SHEET

## Shell GTL Fluid G70

Print Date 16.06.2022

Revision Date 15.06.2022

Version 1.4

CLP = Classification Packaging and Labelling  
COC = Cleveland Open-Cup  
DIN = Deutsches Institut für Normung  
DMEL = Derived Minimal Effect Level  
DNEL = Derived No Effect Level  
DSL = Canada Domestic Substance List  
EC = European Commission  
EC50 = Effective Concentration fifty  
ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals  
ECHA = European Chemicals Agency  
EINECS = The European Inventory of Existing Commercial Chemical Substances  
EL50 = Effective Loading fifty  
ENCS = Japanese Existing and New Chemical Substances Inventory  
EWC = European Waste Code  
GHS = Globally Harmonised System of Classification and Labelling of Chemicals  
IARC = International Agency for Research on Cancer  
IATA = International Air Transport Association  
IC50 = Inhibitory Concentration fifty  
IL50 = Inhibitory Level fifty  
IMDG = International Maritime Dangerous Goods  
INV = Chinese Chemicals Inventory  
IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables  
KECI = Korea Existing Chemicals Inventory  
LC50 = Lethal Concentration fifty  
LD50 = Lethal Dose fifty per cent.  
LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading  
LL50 = Lethal Loading fifty  
MARPOL = International Convention for the Prevention of Pollution From Ships  
NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level  
OE\_HP = Occupational Exposure - High Production Volume  
PBT = Persistent, Bioaccumulative and Toxic  
PICCS = Philippine Inventory of Chemicals and Chemical Substances  
PNEC = Predicted No Effect Concentration  
REACH = Registration Evaluation And Authorisation Of Chemicals  
RID = Regulations Relating to International Carriage of Dangerous Goods by Rail  
SKIN\_DES = Skin Designation  
STEL = Short term exposure limit  
TRA = Targeted Risk Assessment  
TSCA = US Toxic Substances Control Act  
TWA = Time-Weighted Average  
vPvB = very Persistent and very Bioaccumulative

### Further information

# SAFETY DATA SHEET

## Shell GTL Fluid G70

Print Date 16.06.2022

Revision Date 15.06.2022

Version 1.4

Training advice : Provide adequate information, instruction and training for operators.

Other information : This product is intended for use in closed systems only.

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to compile the Safety Data Sheet : The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID data base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.